



# **Affordable Pre-Finishing of SiC for Optical Applications**

**Mirror Technology Days 2009  
Albuquerque, NM**

**Presented by:**


**Odile Clavier, Ph. D., and Jay C. Rozzi, Ph.D.  
Create Inc.**

## **Presentation Outline**

- **Introduction to Create**
- **Background**
- **Innovation**
- **Phase I Results**
- **Program Overview**
- **Summary**

# Creare Incorporated


- “Problem Solvers”
- Contract Engineering R&D
  - Diverse Technical Expertise
  - Extensive Facilities
- Industrial & Federal Client Base
- Founded 1961
- Partnership of Engineers
- Technology Commercialization
  - Licensing
  - Spin-off Companies
  - Custom Products
  - Phase III
- Spinoffs
  - 9 Companies/1900 Employees
  - Revenues \$400 M/year



*Cryocooler for HST*



*Catapult Gap-Width  
Measurement Device*



*Anti-Corrosion Coverings*






# Technology Areas

- Fluid Dynamics & Heat Transfer
- Biomedical
- Cryogenics
- Software & Data Systems
- Manufacturing Technology
- Sensors & Controls

*Miniature High-Speed Turbine*



*Laser-Assisted and Ultra-Precision Machining*




*Automated Assembly for Thermal Batteries*

*Advanced Head/Hearing Protection for Carrier Deck Crews*




*Turnkey High-Performance Data Acquisition and Processing System*




*Microchannel Evaporator for Microprocessor Cooling*

*Image Reconstruction for Virtual Colonoscopy*




Copyright © 2009  
Creare Incorporated  
An unpublished work. All rights reserved.

# Advanced Manufacturing at Creare




**Laser-Assisted Machining**



**Indirect Cooling for High Performance Machining**



**On-Machine Inspection and Tool Path Correction**



**Modeling and Simulation**




**Hybrid Processing for Ceramic Mirrors**



## Silicon Carbide Optics

- **Silicon carbide is an excellent candidate to replace beryllium in lightweight optics**
- **Eliminates toxicity concerns**
- **Lightweight, thermally stable**
- **Cost-effective manufacturing remains a challenge**




## Overall Manufacturing Process



| $R_a$    | Moderate (~2 $\mu\text{m}$ ) | Low (~25 nm)         | Very Low (~5 nm)    |
|----------|------------------------------|----------------------|---------------------|
| Accuracy | $\pm 25 \mu\text{m}$         | $\pm 100 \text{ nm}$ | $\pm 10 \text{ nm}$ |
| MRR      | N/A                          | High/Low             | Low                 |
| Process  | Single Step                  | Multiple Steps       | Single Step         |
| Cost     | \$\$                         | \$\$\$\$             | \$\$                |


# Pre-Finishing Process






## Our Hybrid Machining Approach

- Use single-point diamond turning (SPDT)
- High MRR Process: Spin-turning
- Low MRR Process: Ductile-regime machining (DRM)



*Spin Turner for High MRR Step*




*Demonstrating Low-MRR DRM Process*


## **Phase I Objectives Achieved**

- **Demonstrated Feasibility of Machining CVD SiC**
  - **Successfully machined material to near-optical quality**
  - **Demonstrated use of DRM for low MRR step**
- **Demonstrated Cost Savings**
  - **Completed detailed cost analysis**
  - **Showed that other options are as much 85% higher cost**
- **Developed a Plan to Scale-Up**
  - **Developed the hybrid approach**
  - **Both based on SPDT**
  - **Sufficient to machine optics for NASA**

## Phase I Technical Achievements



**Setup for Low MRR Tests**





**Measured Cutting Forces**


## Phase I Technical Achievements




***Mirror-Like Surface Produced in CVD SiC***



***Tool Wear After ~100 Cuts***



***Wavefront Profile (~40 nm variation)***



***Roughness (~45 nm  $R_a$ )***



# Cost Evaluation


- **Key Assumptions**

- Conical shape ~254 mm in diameter
- 100  $\mu\text{m}$  of material needs to be removed
- Same cost (man and machine) for each process
- Assumed that we need to remove 2.5 times the final  $R_a$  during finishing
- Cutting tools accounted for in estimates


- **Cases Evaluated**

- Create Process (High MRR: 2  $\text{mm}^3/\text{min}$ ,  $R_a \sim 1000 \text{ nm}$ , Low MRR: 0.025  $\text{mm}^3/\text{min}$ ,  $R_a \sim 40 \text{ nm}$ )
- RAP-Based Process (1  $\text{mm}^3/\text{min}$ ,  $R_a \sim 200 \text{ nm}$ )
- Laser Ablation-Based Process (1  $\text{mm}^3/\text{min}$ ,  $R_a \sim 750 \text{ nm}$ )

# Cost Evaluation



# Program Overview




## **Phase II Technical Objectives**

- **Optimize the Hybrid Machining Process**
  - Further develop high MRR process
  - Refine low MRR process
- **Evaluate the Performance**
  - Coupled effects
  - Surface quality, part strength
  - Cost savings
  - Scale up to larger geometries
- **Demonstrate our Approach**
  - Machine a conical mirror (~254 mm diameter) from Trex CVD SiC



## Phase II Technical Objectives and Plan

- **Optimize the Hybrid Machining Process**
  - Further develop high MRR process
  - Refine low MRR process
- **Evaluate the Performance**
  - Coupled effects
  - Surface quality, part strength
  - Cost savings
  - Scale-up to larger geometries
- **Demonstrate our Approach**
  - Machine a conical mirror (~254 mm diameter) from Trex CVD SiC and deliver to NASA





## **Phase II Tasks**

- **Task 1. Set Specifications**
  - Finalize material selections
  - Develop overall goals
- **Task 2. Develop Process**
  - Overall strategy
  - Measurement system design
  - Fixture design, tool mount design, process evaluations
- **Task 3. Test, Evaluate, and Optimize**
  - Test: Shakedown, High MRR, Low MRR, Hybrid
  - Evaluate: SEM Examinations, Accuracy, Roughness, Strength
  - Optimize
- **Task 4. Demonstrate and Deliver**
  - Plan
  - Develop fixtures
  - Demonstrate
  - Deliver

## High MRR Approach for Phase II

- Spin Turner from Edge Tech.
- Rotates to maintain sharp edge at high MRR
- Preliminary approach for high MRR process



## Summary

- **Demonstrated feasibility and cost-effectiveness of our Hybrid Machining Approach**
- **Showed that DRM is viable process for the low-MRR phase**
- **Identified an available approach for the high-MRR process for Phase II**
- **Developed an overall program approach that focuses on commercialization and transition**



## SBIR DATA RIGHTS

These SBIR data are furnished with SBIR rights under Contract No. NNX08CB94P. For a period of 4 years after acceptance of all items to be delivered under this contract, the Government agrees to use these data for Government purposes only, and they shall not be disclosed outside the Government (including disclosure for procurement purposes) during such period without permission of the Contractor, except that, subject to the foregoing use and disclosure prohibitions, such data may be disclosed for use by support Contractors. After the aforesaid 4-year period the Government has a royalty-free license to use, and to authorize others to use on its behalf, these data for Government purposes, but is relieved of all disclosure prohibitions and assumes no liability for unauthorized use of these data by third parties. This Notice shall be affixed to any reproductions of these data, in whole or in part.